

DECLARATION OF PERFORMANCE

Acc.EU No. 305/2011**Ref No: OER-085**

1. Unique identification code of the product-type : **EM 176 EN ISO 18275-A E 62 6 Mn 2NiMo B 42**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) : **Covered electrode ID : 085**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Welding consumable used in metallic structures or in composite metal and concrete structures.**
4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5): **OERLIKON KAYNAK ELEKTRODLARI SANAYI A.S 45030 MANISA / TURKEY**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **NA**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
Notified factory production control certification body number 0035 -TÜV Rheinland Industrie Service GmbH, Am Grauen Stein, D-51105 Köln, Germany- performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control; Certificate no: 0035-CPR-C610. / System 2+
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **NA.**
9. Declared performance : **EN ISO 18275-A E 62 6 Mn 2NiMo B 42**

| | C | Si | Mn | P | S | Cr | Ni | Mo | V | Cu |
|-----|------|------|------|------|------|------|------|------|------|------|
| Min | 0,03 | - | 1,40 | - | - | - | 1,80 | 0,30 | - | - |
| Max | 0,10 | 0,80 | 2,00 | 0,03 | 0,03 | 0,20 | 2,60 | 0,60 | 0,05 | 0,03 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Manisa, 18.09.2024, Rev.5

Emre YILMAZ

Certification Responsible

emre.yilmaz@magemaweld.com